

STOKES BITUMINOUS ALUMINIUM PAINT

Reference AB001	Revision No 1	Revision Date 20 April 2000	Printed 24 January 2008	Page 1 of 2
---------------------------	-------------------------	---------------------------------------	-----------------------------------	--------------------

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>PROPERTIES Waterproof paint for protecting iron and steel, concrete, roofing felt, asbestos and wood. This material exhibits good alkali and acid resistance together with good solar reflective characteristics.</p> <p>USES Water proofing and preserving bituminous coated roofing felt.</p>
Technical Data	<p>TYPE Plasticised bitumen/resin blend.</p> <p>DRYING TIME Within one hour to BS3900 part C3 under normal conditions of temperature and humidity. Recoatable after 2 hours.</p> <p>SPREADING CAPACITY Approximately 12 sq. metres per litre at a dry film thickness of 40 microns on smooth non-porous surfaces.</p> <p>FLASH POINT 32øC to 55øC FLAMMABLE LIQUID.</p> <p>NON VOLATILE CONTENT By volume 50% nominal. By weight 60% nominal.</p> <p>THINNERS AND CLEANING SOLVENT Stokes White Spirit Ref. TH010.</p> <p>HEAT RESISTANCE Up to 80øC.</p> <p>OIL RESISTANCE Good resistance to most lubricating and industrial oils. Tests for suitability with any particular oil should be made before large scale application.</p> <p>CHEMICAL RESISTANCE Good resistance to most common dilute acids and alkalis. Tests should be carried out for resistance to particular agents before attempting large scale application.</p> <p>LEAD CONTENT No added lead.</p> <p>COLOUR RANGE Dull metallic finish. No other colour available.</p>
Stock Container Sizes	5 litres.
Processes	<p>PREPARATION The surface to be painted must be clean, dry and free from grease, dust, dirt, rust, fungus growth and other loose or flaking material.</p> <p>FINISHING Apply one or preferably two coats if a high standard of durability is required.</p>



TECHNICAL DATA SHEET

STOKES BITUMINOUS ALUMINIUM PAINT

Reference AB001	Revision No 1	Revision Date 20 April 2000	Printed 24 January 2008	Page 2 of 2
---------------------------	-------------------------	---------------------------------------	-----------------------------------	--------------------

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Application	<p>BRUSH Supplied ready for use.</p> <p>ROLLER Thinning not normally required.</p> <p>CONVENTIONAL SPRAY Thin as necessary with Stokes White Spirit Ref. TH010.</p> <p>AIRLESS SPRAY Thin as necessary with Stokes White Spirit Ref. TH010.</p>
Storage	<p>Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. CMR).</p>
Health and Safety	<p>THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. CMR FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>
Disclaimer	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>