

QUICK DRYING WHITE SPIRIT BASED ACRYLIC LACQUER

Reference AS001	Revision No 1	Revision Date 17 April 1997	Printed 15 January 2008	Page 1 of 2
---------------------------	-------------------------	---------------------------------------	-----------------------------------	--------------------

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>PROPERTIES Clear quick drying lacquer exhibiting good non-yellowing characteristics.</p> <p>USES Sealer for use on concrete, plaster or other porous masonry surfaces.</p>
Technical Data	<p>TYPE Thermoplastic acrylic resin solution in white spirit.</p> <p>DRYING TIME Approx. 20 - 30 mins. to BS3900 Part C2 under normal conditions of temperature and humidity.</p> <p>THEORETICAL SPREADING CAPACITY About 5.5 sq. metres per litre on smooth non-porous surfaces to achieve a dry film thickness of 25 microns (1 thou).</p> <p>FLASH POINT Between 21 - 55°C FLAMMABLE LIQUID</p> <p>NON VOLATILE CONTENT By volume 14% nominal. By weight 18% nominal.</p> <p>THINNERS AND CLEANING SOLVENT Stokes Thinner Ref. TH010.</p> <p>LEAD CONTENT Does not contain lead.</p> <p>COLOUR RANGE Clear only.</p>
Stock Container Sizes	5 litre containers. Other sizes by special arrangement.
Processes	<p>PREPARATION The surface to be painted must be clean, dry, and free from grease, dust, dirt, rust, peeling, loose material or any other contamination.</p> <p>FINISHING Apply a single coat of the lacquer to the clean substrate. A further coat could be applied if a higher 'build' is required. Allow overnight drying between coats.</p>
Application	<p>BRUSH. Supplied ready for use.</p> <p>ROLLER. Supplied ready for use.</p> <p>CONVENTIONAL SPRAY. Supplied ready for use.</p>
Storage	<p>Use within 24 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. AS001).</p>
Health and Safety	<p>THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. AS001 FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>



TECHNICAL DATA SHEET

QUICK DRYING WHITE SPIRIT BASED ACRYLIC LACQUER

Reference
AS001

Revision No
1

Revision Date
17 April 1997

Printed
15 January 2008

Page 2 of 2

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899

Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.

R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.