



TECHNICAL DATA SHEET

STOKES ANTI-VANDAL PAINT

Reference AV Revision No 1 Revision Date 2 August 1996 Printed 15 January 2008 Page 1 of 2

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>PROPERTIES</p> <p>Stokes Anti-Vandal Paint does not dry and so provides a deterrent to anyone intending to climb or walk on surfaces coated with it. The paint stains skin and clothing and can only be removed with cleansing creams or solvents. The paint does not 'through dry' and does not produce a sticky coating that would harm birds or small pets. Graffiti painting can be easily removed if applied over the Anti-Vandal Paint. However when the graffiti is removed the original Anti-Vandal Paint will also come off.</p> <p>USES.</p> <p>Coating drain pipes, railings, window sills, balustrades, fencing, gates, wall tops and any other features likely to assist climbing or other illegal or irregular means of entry.</p> <p>NOTE : It may be necessary to display a warning notice of the use of Anti-Vandal Paint at levels where the general public might reasonably come into contact with the coating to avoid possible claims of damage to clothing etc.,.</p>
Technical Data	<p>TYPE.</p> <p>Solution of mixed petroleum hydrocarbons with selected pigments.</p> <p>DRYING TIME.</p> <p>Solvent evaporates to leave a 'non-set' finish in about « hour under normal conditions of temperature and humidity.</p> <p>THEORETICAL SPREADING CAPACITY.</p> <p>Approx. 3 sq. metres per litre on smooth non-porous surfaces to achieve a 'dry film' thickness of 300 microns (12 thou.).</p> <p>FLASH POINT.</p> <p>Between 21°C and 55°C. FLAMMABLE LIQUID.</p> <p>NON VOLATILE CONTENT.</p> <p>By volume 87% nominal } Information based on Brilliant White formulation. By weight 90% nominal } For other colours these figures will be slightly reduced.</p> <p>THINNERS AND CLEANING SOLVENT.</p> <p>Stokes White Spirit Ref. TH010.</p> <p>HEAT RESISTANCE.</p> <p>Up to 60°C.</p> <p>LEAD CONTENT.</p> <p>Below 0.25% on Dry Film.</p> <p>COLOUR RANGE.</p> <p>Brilliant White, Black and Grass Green. Other colours by special arrangement.</p>
Stock Container Sizes	<p>5 litre tins only.</p>
Processes	<p>PREPARATION.</p> <p>The surface to be painted must be clean, dry and free from grease, dust, dirt, rust and peeling or loose material. It can however be applied over clean previous painted surfaces.</p> <p>Absorbent surfaces such as masonry, concrete, cement etc. should be first sealed with Stokes Alkali Resisting Primer Sealer Ref. DP004 before application of the Anti-Vandal Paint.</p>
Application	<p>BRUSH.</p> <p>Supplied ready for use. The use of a stiff bristle brush is the preferred method. A coating of approx. 300 microns (12 thou.) should be applied to a suitable deterrent coating.</p>



TECHNICAL DATA SHEET

STOKES ANTI-VANDAL PAINT

Reference
AV

Revision No
1

Revision Date
2 August 1996

Printed
15 January 2008

Page 2 of 2

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Storage	<p>Use within 12 months of receipt of purchase / delivery. Keep in original containers until required for use. Partly used containers should be re-sealed and stored in accordance to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. AV).</p>
Health and Safety	<p>THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF.AV FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>
Disclaimer	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>