

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>Mainly used for Artists materials or for D.I.Y. applications (i.e. such as furniture restoration). Thin films will air dry within 3 - 4 days depending on the ambient temperature. Refined Linseed Oil is the palest colour of these oils, whilst the Boiled Oil possesses the best through drying characteristics.</p> <p>WARNING Before adding any of the various linseed oils to paints or any other materials first check, instructions, technical and materials safety data sheets of the other materials involved.</p>
Technical Data	<p>TYPE. Combination Linolenic acid, Linoleic acid, Oleic acid and saturated fatty acids.</p> <p>FLASH POINT. Above 232°C. (450°F).</p>
Stock Container Sizes	<p>½ litre, 1 litre, 2 litre and 5 litre.</p>
Storage	<p>Use within 24 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. DO).</p>
Health and Safety	<p>THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. DO FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING MEASURES, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>
Disclaimer	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>