

**WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899**  
**Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk**

<b>Properties and Uses</b>	<p><b>PROPERTIES</b> A hard wearing oil based paint giving an attractive silk finish, good build and good opacity. Easy to apply, good wet edge time for large areas and produces excellent flow, free of brush marks.</p> <p><b>USES</b> For use on interior woodwork and walls only. Ideally suited for use in areas where its resistance to abrasion allows washing repeatedly without marking the paint or polishing it.</p>
<b>Technical Data</b>	<p><b>TYPE</b> Long oil modified alkyd medium with carefully selected pigments.</p> <p><b>DRYING TIME</b> 4 - 6 hours to BS3900 part C2 under normal conditions of temperature and humidity. Recoatable after overnight drying.</p> <p><b>THEORETICAL SPREADING CAPACITY</b> About 19 sq. metres per litre on smooth non-porous surfaces to achieve a dry film thickness of 25 microns.</p> <p><b>FLASH POINT</b> In the range 32°C and 55°C. FLAMMABLE LIQUID.</p> <p><b>NON VOLATILE CONTENT</b> By volume 48% nominal. By weight 70% nominal.</p> <p><b>THINNERS AND CLEANING SOLVENT</b> Stokes White Spirit Ref. TH010.</p> <p><b>HEAT RESISTANCE</b> All oil-containing paints such as Stokes Eggshell Finish show some discoloration on heating; the normal changes are summarised below but depend on the length of time for which the surface is heated.</p> <p>Up to 82°C. Usually unaffected. 82°C - 93°C. Some discolouration of pastel shades. 93°C - 150°C. Most colours tend to yellow. Above 150°C. Unsuitable.</p> <p><b>COLOUR RANGE</b> A limited range of colours are available from stock. See shade card. Colours to customers particular requirements are made by special arrangement.</p>
<b>Stock Container Sizes</b>	5 litres, 2½ litres and 1 litre.
<b>Processes</b>	<p><b>PREPARATION</b> The surface to be painted should be clean, dry and free from grease, dust, dirt, rust and peeling or loose material. New plaster, wood, metal and dry porous surfaces must be coated with the appropriate Stokes Primer.</p> <p><b>FINISHING</b> Two coats are necessary for primed surfaces or where a marked colour change is desired. Allow overnight drying of each coat. This Eggshell Finish may be thinned slightly if required using up to 1 part of Stokes White Spirit to 16 parts of paint.</p>



# TECHNICAL DATA SHEET

## STOKES EGGHELL FINISH PAINT

Reference  
DS

Revision No  
1

Revision Date  
22 May 2000

Printed  
15 January 2008

Page 2 of 2

**WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899**  
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

<b>Application</b>	<p><b>BRUSH</b> The Eggshell Finish Paint is supplied ready for use.</p> <p><b>ROLLER</b> Thinning is not normally required. Mohair or foam rollers are preferable to lambswool to achieve a smoother finish.</p> <p><b>CONVENTIONAL SPRAY</b> Thin as necessary with Stokes White Spirit Ref. TH010</p> <p><b>AIRLESS SPRAY</b> Thin as necessary with Stokes White Spirit Ref. TH010.</p> <p><b>ELECTROSTATIC SPRAY</b> For low resistance use Stokes Thinners Ref. TH009.</p>
<b>Storage</b>	<p>Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. DG/DU).</p>
<b>Health and Safety</b>	<p>THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. DG/DU FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>
<b>Disclaimer</b>	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes &amp; Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes &amp; Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>