

STOKES TEAK OIL

Reference DV015	Revision No 1	Revision Date 17 January 1996	Printed 15 January 2008	Page 1 of 1
---------------------------	-------------------------	---	-----------------------------------	--------------------

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>Puts back natural oils into wood and furniture. Helps to prevent wood from drying out, warping and splitting. Surfaces should be clean and dry before applying this product. Apply a thin coat of Stokes Teak Oil with a soft, lint free dry cloth. Work it lightly into the grain of the wood and wipe off any surplus amount of oil.</p>
Technical Data	<p>TYPE. Combination of specially selected vegetable type oils dissolved in an aliphatic hydrocarbon solvent.</p> <p>FLASH POINT. In the range of 21°C - 55°C. FLAMMABLE LIQUID.</p>
Stock Container Sizes	<p>1 litre, 2 litre, 5 litre tins.</p>
Storage	<p>Use within 24 months of delivery. Keep in original container until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of MSDS DV015)</p>
Health and Safety	<p>THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF.DV015 FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>
Disclaimer	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>