

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>PROPERTIES.</p> <p>Stabilises - that is seals and binds - friable, chalking and dusting, concrete, cement rendering, old paint etc., providing a sound substrate for emulsion painting or tiling.</p> <p>USES.</p> <p>Stabilises Interior and Exterior cement rendering, old firmly adhering but powdery paint coatings, asbestos sheeting, powdering brick, stone masonry, plaster and Insulating boards.</p> <p>The prevention of dusting on sound concrete floors is an additional use of this clear primer.</p>
Technical Data	<p>TYPE.</p> <p>Clear Alkali resisting Resin solution.</p> <p>DRYING TIME.</p> <p>4 - 6 hours to BS3900 part C2 under normal conditions of temperature and humidity. Recoatable overnight. This primer must be completely dry before coating with Emulsion paint.</p> <p>THEORETICAL SPREADING CAPACITY.</p> <p>Approx 12 - 13 sq. metres per litre on smooth non-porous surfaces to achieve a dry film thickness of 25 microns (1 thou.)</p> <p>FLASH POINT.</p> <p>Between 32°C and 55°C. FLAMMABLE LIQUID.</p> <p>NON VOLATILE CONTENT.</p> <p>By volume 35% nominal. By weight 43% nominal.</p> <p>THINNERS AND CLEANING SOLVENT.</p> <p>Stokes White Spirit Ref. TH010.</p> <p>LEAD CONTENT.</p> <p>Below 0.5% on the dry film weight.</p> <p>COLOUR RANGE.</p> <p>Supplied as a clear solution.</p>
Stock Container Sizes	<p>1 litre, 5 litre and 25 litre drums.</p>
Processes	<p>PREPARATION.</p> <p>Surfaces must be clean, dry and have no flaking or loose paint or other detachable areas. Mould growth, mildew etc. must be removed by washing with hypochlorite bleach or fungicide prior to applying this stabilising primer.</p>
Application	<p>BRUSH.</p> <p>Supplied ready for use.</p> <p>ROLLER.</p> <p>Supplied ready for use.</p> <p>CONVENTIONAL SPRAY.</p> <p>Supplied ready for use.</p>
Storage	<p>Use within 12 months of delivery.</p> <p>Keep in original containers until required for use.</p> <p>Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of MSDS FS004)</p>
Health and Safety	<p>THIS MATERIAL IS FLAMMABLE.</p> <p>REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. FS004 FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>



TECHNICAL DATA SHEET

STOKES CLEAR STABILISING PRIMER

Reference
FS004

Revision No
1

Revision Date
15 August 1995

Printed
15 January 2008

Page 2 of 2

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899

Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.

R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.