

## STOKES TEREBINE DRIER

<b>Reference</b> MZ011	<b>Revision No</b> 1	<b>Revision Date</b> 2 May 1996	<b>Printed</b> 15 January 2008	<b>Page 1 of 1</b>
---------------------------	-------------------------	------------------------------------	-----------------------------------	--------------------

**WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899**  
**Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk**

<b>Properties and Uses</b>	<p><b>PROPERTIES</b> Increases the rate of drying of many paints and varnishes which dry by oxidation.</p> <p><b>USES.</b> Stokes Terebine Drier revives the drying of old paints and varnishes and improves rates of drying when temperatures are low, as in cold winter months. Note:- Excessive quantities added could increase the tendency of paints to form thick skins on storage particularly in partly used tins of paint.</p>
<b>Technical Data</b>	<p><b>TYPE.</b> Solution of organic metal drier compounds in White Spirit.</p> <p><b>SUGGESTED ADDITION LEVEL.</b> 5 ml per « litre of paint or varnish.</p> <p><b>FLASH POINT.</b> In the range 21øC - 55øC. FLAMMABLE LIQUID.</p> <p><b>Cleaning Solvent.</b> Stokes White Spirit TH010.</p> <p><b>LEAD CONTENT.</b> Below 0.25%</p>
<b>Stock Container Sizes</b>	« litre, 2« litre and 5 litre.
<b>Storage</b>	<p>Use within 24 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Material Safety Data Sheet ref. MZ011).</p>
<b>Health and Safety</b>	THIS MATERIAL IS FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. MZ011 FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROL / PERSONAL PROTECTION AND DISPOSAL.
<b>Disclaimer</b>	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes &amp; Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes &amp; Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>