

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

| | |
|------------------------------|--|
| Properties and Uses | <p>PROPERTIES Intense colour and high tinting strength.</p> <p>USES Stokes pastes are widely used as artists colours.</p> |
| Technical Data | <p>TYPE Traditional concentrated dispersions of pigments in Linseed Oils.</p> <p>DRYING TIME About 24 hours under normal conditions of temperature and humidity. Recoatable after two or three days.</p> <p>SPREADING CAPACITY Approximately 20 sq. metres per litre on smooth non-porous surfaces at nominal dry film thickness of 50 microns (2 thou).</p> <p>FLASH POINT Non Flammable. Will burn above 230°C.</p> <p>NON VOLATILE CONTENT By volume 100%. By weight 100%.</p> <p>THINNERS AND CLEANING SOLVENT Stokes White Spirit Ref. TH010.</p> <p>LEAD CONTENT No Added Lead.</p> <p>COLOUR RANGE Black, Blue, Bright Red, Burnt Turkey Umber, Golden Ochre, Grass Green, Lead Free Lemon, Lead Free Orange, Raw Sienna, Titanium White, Venetian Red and White.</p> |
| Stock Container Sizes | 250 ml, 2.5 litres and 5 litres. |
| Processes | <p>PREPARATION The surface to be painted must be clean, dry and free from grease, dust, dirt, rust and peeling or loose material.</p> |
| Application | <p>BRUSH This as required with Stokes White Spirit Ref. TH010.</p> <p>ROLLER Thin as required with Stokes White Spirit Ref. TH010.</p> <p>PALETTE KNIFE Supplied ready for use.</p> |
| Storage | <p>Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. DO/PC).</p> |
| Health and Safety | REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. DO/PC FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL. |



TECHNICAL DATA SHEET

STOKES COLOUR IN OIL

Reference
PC

Revision No
1

Revision Date
5 June 2000

Printed
15 January 2008

Page 2 of 2

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899

Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Disclaimer

The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.

This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.

R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.