

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Properties and Uses	<p>PROPERTIES Stokes Textured Exterior Emulsion Paint has a long-lasting, attractive textured appearance with elegant low sheen. Self priming on porous surfaces. Excellent obliterating power. Conceals minor imperfections in surfaces. Fast drying, very easy to apply. Contains additive to preserve against mould growth. It can be applied unthinned, or if required thinned with water. Water and weather resistant, hence washable.</p> <p>USES Stokes Textured Exterior Emulsion Paint is recommended for the decoration and protection of interior and exterior wall and ceiling surfaces. It is suitable for kitchens and bathrooms, Plaster, Stone, Concrete, Rendering etc.</p>
Technical Data	<p>TYPE Vinyl Co-polymer Resin with carefully selected pigments.</p> <p>DRYING TIME Within 1 - 2 hours to BS3900 part C2 under normal conditions of temperature and humidity. Recoatable after 2 - 4 hours. The paint will not thoroughly dry at temperatures below 5°C (41°F) or under very humid conditions.</p> <p>FLASH POINT Non Flammable.</p> <p>THEORETICAL SPREADING CAPACITY 8 - 12 sq. metres per litre on smooth non-porous surfaces to achieve a dry film thickness of 50 microns.</p> <p>NON VOLATILE CONTENT By volume 53% nominal. By weight 71% nominal.</p> <p>THINNERS AND CLEANING SOLVENT Water.</p> <p>LEAD CONTENT No Added Lead.</p> <p>COLOUR RANGE TE100 - White. Shades to meet customers special requirements can be supplied by arrangement.</p>
Stock Container Sizes	1, 2.5, 5 & 10 Litre.
Processes	<p>PREPARATION The surface to be painted should be clean, dry and free from grease, dust, dirt, peeling or loose material or any other contamination. Hard gloss surfaces should be well rubbed down to provide a good key. On new but dry plaster, concrete or building boards :- fill cracks, nail or screw holes and sandpaper flat any uneven areas. Seal, screw and nail heads or other ferrous metal fastenings etc. with an Anti-corrosive Primer. Treat any powdery or friable surfaces with Stokes Stabilising Primer Ref FS004. Seal porous surfaces or previously water painted surfaces with one part water to four parts of Stokes Matt Exterior Emulsion Paint, or two parts water if substrate is very porous.</p> <p>FINISHING Apply one coat of Stokes Textured Exterior Emulsion Paint, unthinned, by brush or roller.</p>
Application	<p>BRUSH OR ROLLER For maximum obliteration, apply one coat unthinned. Paint may be thinned one part of water : four parts of paint (by volume), however two coats of paint might then be required to achieve complete obliteration. When applying the unthinned paint by roller, stir the paint to form a smooth fluid consistency before pouring into the roller tray.</p> <p>NOTE Before thinning, stir the paint to a smooth consistency. Add the water slowly, stirring continually. Clean the equipment immediately after use with soap and water.</p>



TECHNICAL DATA SHEET

STOKES TEXTURED EXTERIOR EMULSION

Reference	Revision No	Revision Date	Printed	Page 2 of 2
TE	1	15 February 2001	15 January 2008	

WWW.RJSTOKES.CO.UK MANUFACTURERS OF INDUSTRIAL, DECORATIVE & POWDER COATINGS Est 1899
Little London Road | Sheffield | S8 0UH | Tel: 0114 258 9595 | Fax: 0114 250 9836 | Email: sales@rjstokes.co.uk

Storage	<p>PROTECT FROM FROST Use within 12 months of delivery. Keep in original containers until required for use. Partly used containers should be re-sealed securely and stored according to the recommended manner. (See section 7 of Stokes Material Safety Data Sheet Ref. EML).</p>
Health and Safety	<p>THIS MATERIAL IS NON-FLAMMABLE. REFER TO STOKES MATERIAL SAFETY DATA SHEET REF. EML FOR FULL DETAILS OF FIRST AID, FIRE FIGHTING, ACCIDENTAL RELEASE, HANDLING, EXPOSURE CONTROLS / PERSONAL PROTECTION AND DISPOSAL.</p>
Disclaimer	<p>The above information is for guidance only. It is given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended purpose.</p> <p>This Data Sheet supercedes all previous Data Sheets supplied to you relating to this product. It contains important information which must be communicated to the user. The user must satisfy himself of the suitability of the product for the intended application and surface, as surface and application conditions are beyond the control of R.J.Stokes & Co Ltd. The user must also satisfy himself of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures. Should further information be required, please contact our Technical Department.</p> <p>R.J.Stokes & Co. Ltd. employ a policy of continuous development and the technical data could be revised as a result of experience or new information becoming available.</p>